


AEGIS NFPA



DESCRIPTION

- ▶ Equipped with D-Fuser LED, the AEGIS™ design offers superior 360° output that meets SAE J845 CLASS I & NFPA 1901 zone A upper lighting standards.
- ▶ This 60 inches Lightbar is the ally of choice for the Fire Services.

FEATURES

- ▶ Multi-voltage input: 12Vdc
- ▶ 26 selectable flash patterns
- ▶ High intensity LED modules "D-Fuser" (6 LED modules of 1 Watt per light head)
- ▶ Built-in high intensity scene lights
- ▶ LEDs rated to 100 000 hours of operation
- ▶ Non-volatile memory recalls last flash pattern used at power up
- ▶ Includes traffic arrow option
- ▶ Weatherproof and vibration resistant design for internal or external use
- ▶ Reverse polarity protection
- ▶ Color available: 

ELECTRICAL SPECIFICATIONS

Operating Voltage:	12Vdc
Maximum Current:	32A at 12.8Vdc
Average Current:	16A at 12.8Vdc
Fuse Recommend:	40A


*Consumption in Steady-On mode.

SWITCH CONTROL PANEL



Zone Technologies full equip emergency system

DIMENSIONS



PRODUCT NUMBERS

Number	Description
36902Z	PROSIGNAL - AEGIS D-FUSER/BLACK COVER - 60" RED - SCENE LIGHTS
LB-0435	UNIVERSAL "U" STEEL BRACKETS 1/8" - BLACK (TWO UNITS)
AMPL24-M-0090	FIREMAN SYSTEM WITH SIREN, PA, FUSES & HIGH POWER HARNESS